Customer Details

Company:	Date:
Contact person:	Customer-No.:

Comment (Customer project, based on order, factory standard):

Conveyor System and Quotation

Conveyor type:	Customer request	Quantity:

Conveyed Product and Environmental Conditions

Conveyed product:	Output quantity (units/min):
Dimensions L/B/H (mm):	Total load max. (kg):
Weight each (kg):	Transport position: ⇐ ⇐ chaotic
Sorted: yes no	Sample: yes no

Description conveyed product and environment (temperatures standard +10 up to +60°C, pollutions):

Conveyor Specification

Version:	Total conveyor lenght (mm):

Number of lines:	Line distance (mm):	Line distance center-to-center

Drive version:	Drive location:

Motor orientation:	Voltage: 230/400V 50 Hz Other: TF TH

Speed: m/min at 50 Hz	constant adjustable

Frequency inverter:	Operating mode:

Cycles/min:	Transport time (sec.):	Holding time (sec.):	Conveying path/cycle (mm):

Shift operation:	Power transmission:

Infeed/loading:

Discharge/removal:

Comment:

Transport Medium

Chain type:	
good traction	accumulation	ESD	cut-resistant	oil-resistant	FDA

Cam: Height (mm):   Distance (mm):

Comment:

Stands

Stand selection:	Working height (mm):

Comment:

Side Rails (adjustable only for straight line)

Side rail type:	Side rail strips:
Height of side rail (mm):	Usable width (mm):

Side rail side: both sides   one-sided right   one-sided left

Comment:

Documentation/Drawing

Additional documentation (standard German or national language paper + PDF):

Approval drawing (standard STEP):   no   yes

Comment (non-standard version, factory standard, etc.):

Function Description and Additional Equipment

Sketch